

CEKA ATTACHMENTS PRECI-LINE

*Your partner for
precision attachments*



CATALOGUE

More at:

WWW.CEKA-PRECILINE.COM

Ask for instruction leaflets
or download from
www.ceka-preciline.com

CEKA
ATTACHMENTS
PRECI-LINE

WWW.CEKA-PRECI-LINE.COM



- Complete catalogue
- All brochures in pdf
- Service and Aftercare
- Safety Data Sheets
- Instructions for use
- FAQ's
- Old spring pins
- ISO/CE certificates
- Promotions

Copyright© ALPHADENT NV 6/2011. No part of this brochure may be reproduced in any manner without permission of ALPHADENT NV. Our products are subject to continuous development. We therefore reserve the right to make technical changes without preliminary notice.

CEKA, CEKA REVAX, PRECI-LINE, PRECI-VERTEX and PRECI-HORIX are registered trademarks of ALPHADENT NV.

CEKA® ATTACHMENTS

M2 size (2 mm)



**M2 size male spring pin
RE 0031**

Height: 2.7 mm
2 pcs + 2 space maintainers

M3 size (3 mm)



**M3 size male spring pin
694 C**

Height: 3.15 mm
2 pcs + 2 space maintainers

CEKA REVAX – EXTRACORONAL GREEN

M2: H 3.80 mm - ø 3.4 mm
M3: H 4.35 mm - ø 4.4 mm

Female for bonding with CEKA SITE. Use any dental alloy.

Male for bonding with CEKA SITE **(A)**, winged acrylic fixation **(B)**, soldering with CEKA SOL **(C)** or circular acrylic fixation **(D)**.

Each package contains 1 attachment and 3 different plastic profiles (30°, 45°, 60°) to choose from.

See page 6 for individual components, including laser components.



M2 size: **RE 0185 TI**
M3 size: **OL 0285 TI**

M2 size: **RE 0175 TI**
M3 size: **OL 0275 TI**

M2 size: **RE 0161 TI**
M3 size: **OL 0261 TI**

M2 size: **RE 0195 TI**
M3 size: **OL 0295 TI**

NEW

CEKA REVAX – EXTRACORONAL BLUE

M2: H 3.80 mm - ø 3.4 mm
M3: H 4.35 mm - ø 4.4 mm

Female for the cast-on technique with non-precious alloys.

Male for bonding with CEKA SITE **(A)**, winged acrylic fixation **(B)**, soldering with CEKA SOL **(C)** or circular acrylic fixation **(D)**.

Each package contains 1 attachment and 3 different plastic profiles (30°, 45°, 60°) to choose from.

See page 6 for individual components, including laser components.



M2 size: **RE 0185 NP**
M3 size: **OL 0285 NP**

M2 size: **RE 0175 NP**
M3 size: **OL 0275 NP**

M2 size: **RE 0161 NP**
M3 size: **OL 0261 NP**

M2 size: **RE 0195 NP**
M3 size: **OL 0295 NP**

NEW

CEKA REVAX – EXTRACORONAL ORANGE

M2: H 3.80 mm - ø 3.4 mm
M3: H 4.35 mm - ø 4.4 mm

Female for the cast-on technique with precious alloys.

Male for bonding with CEKA SITE **(A)**, acrylic fixation **(B)**, soldering with CEKA SOL **(C)** or circular acrylic fixation **(D)**.

Each package contains 1 attachment and 3 different plastic profiles (30°, 45°, 60°) to choose from.

See page 6 for individual components, including laser components.



M2 size: **RE 0185 IR**
M3 size: **OL 0285 IR**

M2 size: **RE 0175 IR**
M3 size: **OL 0275 IR**

M2 size: **RE 0161 IR**
M3 size: **OL 0261 IR**

M2 size: **RE 0195 IR**
M3 size: **OL 0295 IR**

NEW

CEKA – AXIAL

M2: H 3.6 mm - ø 3.4 mm
M3: H 4.0 mm - ø 4.2 mm

Female for acrylic fixation in the removable prosthesis.

Male on post-coping: for soldering with CEKA SOL FILIGRAN **(A)** or for the cast-on technique with precious alloys **(B)**.

Each package contains 1 attachment. See page 6 for individual components, including laser components.



A

M2 size: **RA 61 TI**
M3 size: **691 TI**



B

M2 size: **RA 63 TI**
M3 size: **693 TI**

CEKA – AXIAL & BAR CONSTRUCTIONS

M2: H 3.80 mm - ø 3.4 mm
M3: H 4.35 mm - ø 4.4 mm

Female for bonding with CEKA SITE in post-copings or in bar constructions (all alloys).


Male for bonding with CEKA SITE **(A)** or for acrylic fixation **(B)**.

Each package contains 1 attachment. See page 6 for individual components, including laser components.



A

M2 size: **RE 0785 TI**
M3 size: **OL 0885 TI**



B

M2 size: **RE 0795 TI**
M3 size: **OL 0895 TI**

CEKA ID


M2: H 4.65 mm - ø 3.2 mm
M3: H 4.80 mm - ø 4.0 mm

Intracoronary CEKA combination attachment for the cast-on technique with precious alloys.

A 0.3 mm space maintainer prevents uncontrolled forces from acting on the extracoronary female.

Each package contains 1 attachment. See page 6 for individual components.

Use the P 9 paralleling mandrel.



M2 size: **RE 0703 IR**
M3 size: **703 IR**

CEKA 334

H 4.4 mm - ø 4.3 mm

Female for the cast-on technique with non-precious alloys.

Male for the bolt-on technique in the cast metal partial frame.

See page 6 for individual components.



M3 size only: **OL 334 NX**

2 attachments/package



M3 size only: **OL 0234 NPR**

1 attachment/package
Includes 60° profile only.

Female for the cast-on technique with non-precious alloys (blue), precious alloys (orange), or any dental alloy (yellow).
 Male for bonding with CEKA SITE (A), acrylic fixation (B) or for soldering with CEKA SOL FILIGRAN (C).
 Each package contains 2 attachments in one bar profile.
 See page 6 for individual components, including laser components.



CEKA KITS



NEW

LABORATORY TOOL KIT* # REVAX LK 3
Contents: H 1, H 13, H 14, H 16, H 2, H 30, P 7, P 8, RE H 1, RE H 10, RE H 13, RE H 14, RE H 16, RE H 2, RE H 5, RE H 79, RE P 2/5, RE P 7, A 1, AF 69, 694 C, RE 0031

REDUCED LABORATORY TOOL KIT # REVAX RK 3
Contents: H 1, H 13, H 14, H 16, H 2, P 7, P 8, RE H 1, RE H 10, RE H 13, RE H 14, RE H 16, RE H 2, RE H 5, RE P 2/5, RE P 7


























DENTIST TOOL KIT # REVAX OK 2
Contents: AF 69, A 1, H 30, RE H 5, RE H 79, RE 0031, 694 C, 724 C

SPRING PIN KIT M2 & M3 # REVAX SP 1**
Contents: RE 0031, RE 0031 L, RE 0031 195, 694 C, 694 C/L, 694 C/195, 694 C/202, 694 C/209, AF 69, A 1, RE H 5, CB1, H 30

SPRING PIN KIT M2 # REVAX SP 2
Contents: RE 0031, RE 0031 L, RE 0031 195, A 1, RE H 5, CB1, H 30

SPRING PIN KIT M3 # REVAX SP 3
Contents: 694 C, 694 C/L, 694 C/195, 694 C/202, 694 C/209, AF 69, A 1, RE H 5, CB1, H 30

CEKA INDIVIDUAL COMPONENTS*

- ①  M2 size: **RE 0085**
M3 size: **694 AR**
Retention part for bonding with CEKA SITE.
Including duplicating dummy.
TITANAX alloy - 2 + 2 pcs
- ②  M2 size: **RE 0075**
M3 size: **694 AKS**
Retention part for winged acrylic fixation
TITANAX alloy - 2 pcs
- ③  M2 size: **RE 0095**
M3 size: **694 AKS2**
Retention part for circular acrylic fixation
TITANAX alloy - 2 pcs
- ④  M2 size: **RE 0061**
M3 size: **694 AS**
Retention part for soldering with CEKA SOL
PALLAX alloy - 2 pcs
- NEW**  M2 size: **RE 0065**
M3 size: **694 AL**
Retention part for the laser technique
PURE TITANIUM - 2 pcs
- ⑤  M2 size: **RE 0031**
M3 size: **694 C**
Male spring pin. Use CEKA BOND to prevent
gradual unthreading.
PALLAX alloy - 2 pcs + 2 space maintainers
-  M3 size only: **724 C**
Rigid male spring pin. Use CEKA BOND to
prevent gradual unthreading.
PALLAX alloy - 2 pcs
- ⑥  M2 size: **RE 0096**
M3 size: **694 B**
Space maintainer of 0.3 mm thickness
STAINLESS STEEL - 10 pcs
- ⑦  M2 size: **RE 0100 TI**
M3 size: **OL 0200 TI**
Female for bonding with CEKA SITE.
Use any dental alloy.
TITANAX alloy - 1 + 3 pcs
- ⑧  M2 size: **RE 0100 NP**
M3 size: **OL 0200 NP**
Female for the cast-on technique with
non-precious alloys
NOPRAX alloy - 1 + 3 pcs
- ⑨  M2 size: **RE 0100 IR**
M3 size: **OL 0200 IR**
Female for the cast-on technique with
precious alloys
IRAX alloy - 1 + 3 pcs
- ⑩  M2 size: **RA 0061**
M3 size: **691 D**
Base ring for soldering with
CEKA SOL FILIGRAN
PALLAX alloy - 1 pc
- ⑪  M2 size: **RA 0063**
M3 size: **693 D**
Base ring for direct casting with
precious alloys
IRAX alloy - 1 pc
- NEW**  M2 size: **RA 0064**
M3 size: **693 DNX**
Base ring for direct casting with
non-precious alloys
NOPRAX alloy - 1 pc
- ⑫  M2 size: **RA 0091**
M3 size: **691 A**
Female for retention in acrylic overdentures
TITANAX alloy - 1 pc
- ⑬  M2 size: **RA 0055**
M3 size: **691 E**
Large space maintainer for post-copings
TINFOIL - 1 pc
- ⑭  M2 size: **RE 0700 TI**
M3 size: **OL 0800 TI**
Female for bonding with CEKA SITE
in post-copings or in bar constructions
TITANAX alloy - 1 + 1 pc
- ⑮  M3 size only: **OL 694 DNX**
Female for the cast-on technique with
non-precious alloys
NOPRAX alloy - 1 pc
- ⑯  M3 size only: **OL 694 D**
Female for the cast-on technique with
precious alloys
IRAX alloy - 1 pc
- ⑰  M3 size only: **OL 694 DPR**
Female for the cast-on technique with
any dental alloy
PLATIRAX alloy - 1 pc
- ⑱  M3 size only: **334 A**
Retention nut for 334 C
TITANAX alloy - 1 pc
- ⑲  M3 size only: **334 C**
334 male spring pin for the bolt-on technique
PALLAX alloy - 1 pc
- ⑳  M3 size only: **334 F**
Burn-out plastic ring for the bolt-on technique
1 pc
- ㉑  M2 size: **RE 0083 IR**
M3 size: **703 A**
CEKA ID retention part for soldering with
CEKA SOL
IRAX alloy - 1 pc
- ㉒  M2 size: **RE 0053 IR**
M3 size: **703 D**
Female for CEKA ID for the cast-on
technique with precious alloys
IRAX alloy - 1 pc

OVERSIZED MALE SPRING PINS*



M2 size spring pin (PALLAX alloy)
with larger head (ø 1.95 mm)
RE 0031 195 **2 pcs**



M2 size spring pin (gold-plated PALLAX alloy)
extra long (0.3 mm longer)
RE 0031 L **2 pcs**



M3 size spring pin (PALLAX alloy) with larger
head (ø 1.95 mm, 2.02 mm, 2.09 mm)
694 C/195 **2 pcs**
694 C/202 **2 pcs**
694 C/209 **2 pcs**



M3 size spring pin (PALLAX alloy)
extra long (0.3 mm longer)
694 C/L **2 pcs**



Rigid M3 size spring pin (PALLAX alloy) with
larger head (ø 1.95 mm, 2.02 mm, 2.09 mm)
724 C/195 **2 pcs**
724 C/202 **2 pcs**
724 C/209 **2 pcs**



M3 size spacer disc (PALLAX alloy),
to lengthen the spring pin. Use maximum
5 discs. Use also CEKA BOND.
AF 69 0.05 mm thick **10 pcs**

Old spring pins are still available. See separate leaflet no 98.E or www.ceka-preciline.com.

UNIVERSAL ACCESSORIES M2 AND M3 SIZE



M2 & M3 size: **RE H 5**
Laboratory key



M2 & M3 size: **P 8**
Paralleling mandrel and sandblasting tool
for TITANAX females



M2 & M3 size: **A 1**
Activating tool and screw-driver




M2 & M3 size: **RE P 2/5**
Paralleling mandrel for females



M2 & M3 size: **RE H 79**
Instrument for retention reduction



M2 & M3 size: **RE H 20**
Diamond burr for the bonding technique
2 pcs



M2 & M3 size: **H 30**
Set of 4 profiles to indicate the diameter
of the females



M2 & M3 size: **RE H 10**
Carbide burr with smooth stop for the
metal sleeve

CEKA SITE
CEKA BOND
See page 18.



M2 & M3 size: **P 9**
Paralleling mandrel for CEKA ID

ACCESSORIES M2 OR M3 SIZE



M2 size: **RE P 7**
M3 size: **P 7**
Paralleling mandrel for green
female keepers



M2 size: **RE P 4**
M3 size: **P 4**
Paralleling mandrel for axial base rings



M2 size: **RE H 2** **2 pcs**
M3 size: **H 2** **2 pcs**
Impression tool for axial attachments,
to be used with the (RE) H 14



M2 size: **RE H 14** **2 + 2 pcs**
M3 size: **H 14** **2 + 2 pcs**
Impression tool for females, to be used
with the spring pin, the space maintainer
and the (RE) H 13.
Combine also with the (RE) H 2.



NEW

M2 size: **RE H 17** **2 pcs**
M3 size: **H 17** **2 pcs**
Protection cap in TITANAX alloy for
threading into the base ring



M2 size: **RE H 13** **2 pcs**
M3 size: **H 13** **2 pcs**
Female analogue for the repair
and rebasing technique



M2 size: **RE H 1** **2 pcs**
M3 size: **H 1** **2 pcs**
Dummy spring pin with incorporated
space maintainer



M2 size: **RE H 16** **2 pcs**
M3 size: **H 16** **2 pcs**
Soldering accessory for extracoronary
retention parts



M2 size: **RE H 4** **2 pcs**
M3 size: **H 4** **2 pcs**
Soldering accessory for axial base rings

* See page 19 for table of alloys and materials.


PRECI-VERTIX®

Extracoronary slide attachment with burn-out plastic male.
The elastic females are easily replaceable and available in three friction levels.
PRECI-VERTIX has easy procedures and minimal servicing.
It gives excellent patient comfort and can be used with anterior abutments for optimum esthetics.
To be used with any dental alloy. All tools included. Over 30 years of clinical experience.




PRECI-VERTIX STANDARD # 1801 KIT

6 males with attached paralleling mandrel
6 yellow females
1 insertion tool



PRECI-VERTIX P # 1811 KIT

6 angled males for best abutment and tissue contours
6 yellow females
1 paralleling mandrel
1 insertion tool



PRECI-VERTIX P COMBI # 1812 KIT

2 angled males for best abutment and tissue contours
2 + 2 + 2 females
2 castable housings
1 paralleling mandrel
1 insertion tool

INDIVIDUAL COMPONENTS* & ACCESSORIES

PRECI-VERTIX FEMALE

Polypropylene
Height: 5 mm (may be reduced) - ø 3.30 mm
Available in three friction levels:

normal friction:
1802 **yellow** 6 pcs
1802B **yellow** 50 pcs
reduced friction:
1805 **white** 6 pcs
1805B **white** 50 pcs
increased friction:
1806 **red** 6 pcs
1806B **red** 50 pcs
combination package:
1807 2 + 2 + 2 pcs



PRECI-VERTIX HOUSING

Thin plastic female housing for casting and to incorporate with the soldering, bonding or acrylic fixation technique.
To be adjusted according to the male length. Process the housing with the white female and replace the latter after finishing with the final female. Sandblast the inside with coarse aluminous oxide.
Height: 7 mm - Length: 12 mm
Extension height: 5 mm - ø 4.1 mm
1808 6 pcs
1808B 50 pcs



PRECI-VERTIX STANDARD MALE

Male with extension as paralleling mandrel. Remove the extension with a hot instrument after positioning. Cast in any hard alloy. Round the occlusal aspect of the male after processing.
Height: 5.9 mm (may be reduced up to 3 mm)
ø 1.8 mm
1803 6 pcs
1803B 50 pcs




PRECI-VERTIX INSERTION TOOL

Double sided insertion tool for the 3 female types
1804 1 pc



PRECI-VERTIX P MALE

Male with 45° inclination for maximum incorporation possibilities and a periodontal friendly design. Cast in any hard alloy. Round the occlusal aspect of the male after processing.
Height: 5.9 mm (may be reduced to 3 mm)
ø 1.8 mm
1813 6 pcs + paralleling mandrel
1813B 50 pcs



PRECI-VERTIX MALE ANALOGUE

Brass male analogue, for repairs or for making a new prosthesis
Height: 9 mm - ø 1.8 mm
1819 2 pcs



PRECI-VERTIX PARALLELING MANDREL

Adjustable metal paralleling mandrel for frequent users of PRECI-VERTIX P and AT
Groove width: 1.1 mm
ø paralleling mandrel: 2.35 mm
1845 1 pc



Extracoronary friction slide attachment.
The friction of the titanium female can be progressively adjusted with a screw and a plastic friction part.
Good lateral stabilization.
Supplied with a duplicating dummy for bonding with CEKA SITE (female) and a paralleling mandrel.



PRECI-VERTIX AT K
1820 **KIT**
1 burn-out plastic male
1 titanium female with screw and friction part
1 duplicating dummy
1 paralleling mandrel



PRECI-VERTIX AT M
1821 **KIT**
1 cast-on male for precious alloys
1 titanium female with screw and friction part
1 duplicating dummy
1 paralleling mandrel

INDIVIDUAL COMPONENTS* & ACCESSORIES



PRECI-VERTIX AT DUPLICATING DUMMY
Plastic duplicating dummy to prepare the refractory model of the cast metal partial frame for bonding with CEKA SITE
Height: 4.5 mm - Length: 6.1 mm
Width: 3.1 mm
1827 **6 pcs**



PRECI-VERTIX PARALLELING MANDREL
Adjustable metal paralleling mandrel for frequent users of PRECI-VERTIX AT and P
Groove width: 1.1 mm
ø paralleling mandrel: 2.35 mm
1845 **1 pc**




PRECI-VERTIX AT FEMALE
Female in TITANAX alloy with screw and friction part.
May be reduced by 1 mm at tissue side.
Height: 4.4 mm - Length: 6 mm
Width: 2.6 mm
1826 **1 pc**



PRECI-VERTIX AT SCREW-DRIVER
Sterilizable screw-driver for the activating screw
Blade: 0.3 mm - Total length: 30 mm
Handle length: 17.5 mm - ø 1.1 mm
1829 **1 pc**



PRECI-VERTIX AT ACTIVATING SCREW
Screw in TITANAX alloy to activate the friction part
Height: 3 mm - Slot: 0.3 mm - M 1.4
1828 **1 pc**



PRECI-VERTIX AT MALE ANALOGUE
Brass male analogue, for repairs or when making a new prosthesis
Height: 9 mm - ø 1.8 mm
1819 **2 pcs**



PRECI-VERTIX AT FRICTION PART
Removable plastic friction part.
Yellow for adjustment of normal friction.
Red for adjustment of increased friction.
Acetal homopolymer - Height: 3.75 mm
1822 **yellow** **6 pcs**
1822R **red** **6 pcs**

CEKA SITE
CEKA BOND
See page 18.



PRECI-VERTIX AT K MALE
Burn-out plastic male.
May be reduced by 1 mm at tissue side.
Cast in any hard alloy.
Height: 4 mm - ø 1.78 mm
1824 **6 pcs**



PRECI-VERTIX AT M MALE
Male in the high-fusing IRAX alloy for direct casting with precious alloys.
May be reduced by 1 mm at tissue side.
Height: 4 mm - ø 1.78 mm
1823 **1 pc**

* See page 19 for table of alloys and materials.

Sagittal ball attachment with segmented female for partial dentures and implant bar applications. The replaceable plastic female in three retention levels is incorporated directly into the framework. The male is in plastic and cast in a hard alloy, in metal and cast-on with a non-precious alloy, or threaded into a cast-on base ring. PRECI-SAGIX is available in two ball sizes: Mini 1.7 mm and Standard 2.2 mm.

PATENTED



PRECI-SAGIX INTRO KIT P

Introduction kit with **castable plastic males**, the necessary tools and females in three different retention levels for Mini size 1.7 and Standard size 2.2. Cast the males in any hard dental alloy.

22-piece kit:

- 2 + 2 castable **plastic** males
- 2 + 2 yellow females (normal retention)
- 2 + 2 white females (reduced retention)
- 2 + 2 red females (increased retention)
- 2 + 2 duplicating dummies/processing females
- 1 universal paralleling mandrel
- 1 universal insertion tool

Intro kit castable male: # 1301

PRECI-SAGIX INTRO KIT M

Introduction kit with **cast-on NOPRAX males**, the necessary tools and females in three different retention levels for Mini size 1.7 and Standard size 2.2. Cast-on technique for non-precious alloys.

22-piece kit:

- 2 + 2 cast-on **NOPRAX** males
- 2 + 2 yellow females (normal retention)
- 2 + 2 white females (reduced retention)
- 2 + 2 red females (increased retention)
- 2 + 2 duplicating dummies/processing females
- 1 universal paralleling mandrel
- 1 universal insertion tool

Intro kit cast-on male: # 1303

INDIVIDUAL COMPONENTS* & ACCESSORIES

PRECI-SAGIX FEMALE

Polyacetal

Mini size 1.7: height: 3.1 mm - ø 3.1 mm

yellow - normal retention: # 1311 6 pcs # 1311B 50 pcs

white - reduced retention: # 1312 6 pcs # 1312B 50 pcs

red - increased retention: # 1313 6 pcs # 1313B 50 pcs

combination package: # 1314 2 + 2 + 2 pcs

Standard size 2.2: height: 4.1 mm - ø 4.2 mm

yellow - normal retention: # 1361 6 pcs # 1361B 50 pcs

white - reduced retention: # 1362 6 pcs # 1362B 50 pcs

red - increased retention: # 1363 6 pcs # 1363B 50 pcs

combination package: # 1364 2 + 2 + 2 pcs



PRECI-SAGIX DUPLICATING DUMMY / PROCESSING FEMALE

Mini size 1.7: # 1316 6 pcs # 1316B 50 pcs

Standard size 2.2: # 1366 6 pcs # 1366B 50 pcs



PRECI-SAGIX MALE P

Castable spherical plastic male.

Cast in a hard alloy.

Mini size 1.7: # 1321 6 pcs # 1321B 50 pcs

Standard size 2.2: # 1371 6 pcs # 1371B 50 pcs



PRECI-SAGIX MALE M

NOPRAX male for cast-on technique with non-precious alloys

Mini size 1.7: # 1322 2 pcs # 1322B 20 pcs

Standard size 2.2: # 1372 2 pcs # 1372B 20 pcs



PRECI-SAGIX MALE V

NOPRAX Standard male ø 2.2 mm with M2 threading and 0.9 mm internal hex.

Use the IMP-XS-042 screw-driver. # 1373 1 pc



PRECI-SAGIX BASE RING

For cast-on technique in IRAX (with precious alloys) or in NOPRAX (with non-precious alloys).

M2 threading for the 1373 Standard male

ø 2.2 mm

RA 0063 IRAX ALLOY 1 pc

RA 0064 NOPRAX ALLOY 1 pc



NEW

PRECI-SAGIX HOUSING

Cr-Co female housing (Co 65 - Cr 28 - Mo 6) for incorporation into acrylic resin, for soldering with CEKA SOL or for the laser technique.

Mini size 1.7:

height: 3.3 mm - width: 3.8 mm - length: 9.1 mm # 1325 2 pcs # 1325B 20 pcs

Standard size 2.2:

height: 4.5 mm - width: 4.9 mm - length: 9.5 mm # 1375 2 pcs # 1375B 20 pcs



PRECI-SAGIX PARALLELING MANDREL MALE

Universal paralleling mandrel for the PRECI-SAGIX males

1300 P for ø 1.7 and 2.2 1 pc



PRECI-SAGIX SCREW-DRIVER FOR THREADED MALE

Total length: 26 mm - External hex: 0.9 mm

IMP-XS-042 1 pc



CEKA BOND

Anaerobic adhesive to prevent gradual unthreading of the male.

CB1 5 ml



PRECI-SAGIX INSERTION TOOL

Universal insertion tool for the PRECI-SAGIX females

1323 for ø 1.7 and 2.2 1 pc



PLASTICWAX 8° PROFILE

Height: 4.5 mm - Length: 60 mm

Width top: 1.9 mm / bottom: 2.8 mm

IMP-CK-014 4 pcs



PRECI-SAGIX ANALOGUE

Model analogue of male

1331 for ø 1.7 2 pcs

1381 for ø 2.2 2 pcs



PRECI-BALL

H 3.55 mm - 4.35 mm
ø 3.5 mm

Resilient adjustable ball attachment. The 2.25 mm ball diameter makes PRECI-BALL compatible with most implant systems. The male can be soldered, threaded or cast. The female is available in gold alloy or titanium. See page 12 for individual components.



PRECI-BALL STANDARD OR/OR # 1201
Gold female for acrylic fixation and gold male for soldering with CEKA SOL FILIGRAN to the post-coping



PRECI-BALL STANDARD TI/PA # 1203
Titanium female for acrylic fixation and palladium male for soldering with CEKA SOL FILIGRAN to the post-coping



PRECI-BALL PC # 1205
Titanium female for acrylic fixation and burn-out plastic male for casting



PRECI-BALL CV # 1206
Gold female for acrylic fixation and removable titanium male with high-fusing base ring for direct casting with precious alloys

PRECI-CLIX RADICULAR

Chairside ball attachment for acrylic resin overdentures with replaceable plastic female in three retention levels. The female can be incorporated into acrylic resin or directly into the framework. The titanium post is available in two versions: with removable male or with the spherical male in one piece. See page 12 for individual components.



PRECI-CLIX RTI # 1291
Female housing for incorporation into acrylic resin. Cementable titanium post with removable titanium male.



PRECI-CLIX RP # 1292
Replaceable plastic female and duplicating dummy for cast metal partial frames. Cementable titanium post with removable titanium male.

NEW



PRECI-CLIX RCT # 1293
Female housing for incorporation into acrylic resin. Cementable titanium post with titanium male.

NEW



PRECI-CLIX RCP # 1294
Replaceable plastic female and duplicating dummy for cast metal partial frames. Cementable titanium post with titanium male.



PRECI-CLIX DENTIST KIT # 1299

Contains 2 radicular PRECI-CLIX RTI ball attachments, all necessary accessories and spare parts.

Set:
2 x 1291 radicular PRECI-CLIX RTI ball attachments
1 x 1226 set of 3 reamers
1 x 1222 insertion tool
1 x IMP-XS-042 screw-driver
1 x RE H 2 impression tool (2 pcs)
1 x RE H 14 model analogue (2 pcs)
1 x 1234 replacement females (3 x 2 pcs)
1 x CEKA BOND anaerobic adhesive to prevent gradual unthreading of the male part

NEW



PRECI-CLIX RC DENTIST KIT # 1297

Contains 2 radicular PRECI-CLIX RCT ball attachments, all necessary accessories and spare parts.


Set:
2 x 1293 radicular PRECI-CLIX RCT ball attachments
1 x 1226 set of 3 reamers
1 x 1222 insertion tool
1 x 1201 D male analogue
1 x 1234 replacement females (3 x 2 pcs)

* See page 19 for table of alloys and materials.

PRECI-CLIX AXIAL

H 3.4 mm - 4.1 mm
ø 3.55 mm - 4 mm

Axial ball attachment for acrylic resin overdentures with replaceable plastic female in three retention levels. The female can be incorporated into acrylic resin or directly into the framework. The male can either be threaded or cast in any hard alloy.



PRECI-CLIX ATI # 1251
Female housing for incorporation into acrylic resin.
Plastic male for incorporation into post-copings.
Cast in any hard alloy.



PRECI-CLIX AP # 1252
Female duplicating dummy for cast metal partial frames.
Plastic male for incorporation into post-copings.
Cast in any hard alloy.



PRECI-CLIX CV # 1261
Female housing for incorporation into acrylic resin.
Removable titanium male with high-fusing base ring for casting with precious alloys.

PRECI-CLIX EXTRACORONAL

H 5.1 mm - 5.3 mm
ø 3.4 mm

Periodontal friendly ball attachment for extracoronar and bar constructions with replaceable plastic female in three retention levels. The female can be incorporated into acrylic resin or directly into the framework. The male can be incorporated into the preferred profile by bonding with CEKA SITE, as a threaded component or as a burn-out component. To be used with any hard alloy. 1 attachment including 4 profiles/package



PRECI-CLIX TI-TI # 1271
Titanium housing for incorporation into acrylic resin.
Titanium male for cementing in the cast male keeper.



PRECI-CLIX TI-V # 1276
Titanium housing for incorporation into acrylic resin.
Removable titanium male and cementable threading to incorporate.



PRECI-CLIX TI-P # 1281
Titanium housing for incorporation into acrylic resin.
Plastic male to assemble with the male keeper for casting in any hard alloy.



PRECI-CLIX P-TI # 1272
Female duplicating dummy for cast metal partial frames.
Titanium male for cementing in the cast male keeper.



PRECI-CLIX P-V # 1277
Female duplicating dummy for cast metal partial frames.
Removable titanium male and cementable threading to incorporate.



PRECI-CLIX P-P # 1282
Female duplicating dummy for cast metal partial frames.
Plastic male to assemble with the male keeper for casting in any hard alloy.

PRECI-BALL/CLIX - INDIVIDUAL COMPONENTS* & ACCESSORIES



PRECI-BALL FEMALE
Female in TITANAX or in ORAX alloy for acrylic fixation
Height: 2.8 mm - ø 3 mm
1205 A TITANAX ALLOY 1 pc
1205 AB TITANAX ALLOY 20 pcs
1201 A ORAX ALLOY 1 pc
1201 AB ORAX ALLOY 20 pcs
1201 B processing ring 1 pc



PRECI-CLIX HOUSING
Female housing in an anodized titanium alloy for fixation in acrylic resin dentures
Height: 2.65 mm - ø 4 mm
1235 6 pcs
1235B 50 pcs



PRECI-BALL/CLIX LARGE SPACE MAINTAINER
TINFOIL - Thickness: 0.4 mm - ø 14 mm
1201 E 1 pc



PRECI-CLIX FEMALE
Polyacetal - Height: 2.65 mm - ø 3.55 mm
Normal retention:
1231 yellow 6 pcs
1231B yellow 50 pcs
Reduced retention:
1232 white 6 pcs
1232B white 50 pcs
Increased retention:
1233 red 6 pcs
1233B red 50 pcs
Combination package:
1234 2 + 2 + 2 pcs



PRECI-CLIX DUPLICATING DUMMY
Plastic duplicating dummy for cast metal partial frames. No need for a space maintainer!
Height: 2.8 mm - ø 3.55 mm
1236 **6 pcs**



PRECI-CLIX SPACE MAINTAINER
Elastic space maintainer, to be placed between male and female during processing
Rubber - Height: 0.7 mm - ø 1.8 mm
1251 B **6 pcs**



PRECI-CLIX THREADS TI
M2 threading in TITANAX alloy for cementing with CEKA SITE.
Combine with the 1206 C PRECI-CLIX male V.
Height: 1.9 mm - ø 2.3 mm
RE 4600 TI **1 pc**



PRECI-CLIX MALE KEEPER
4 burn-out plastic male keepers for extracoronar and bar constructions
Adaptable in form and height
Internal ø 2.35 mm - External ø 3.4 mm
RE 04 TI **1 x 0°, 1 x 30°, 1 x 45°, 1 x 60°**



PRECI-CLIX POST
Cementable post in TITANAX alloy with threaded base for the 1206 C PRECI-CLIX male V or with attached ball
Post length: 7 mm (may be reduced) - ø 1.35 mm
ø base: 3.4 mm - Threads: M2 - ø ball: 2.25 mm
1291 C **with threads 1 pc**
1293 C **with ball 1 pc**



PRECI-CLIX-R BURR SET
Set of 3 calibrated burs for right angle.
Used for root preparation prior to cementation of the PRECI-CLIX post.
1226 **Set: 1 predrilling burr, 1 cavity burr, 1 precision reamer**
1227 **1 predrilling burr**
1228 **1 cavity burr**
1229 **1 precision reamer**



PRECI-BALL MALE
Spherical male in ORAX alloy (yellow) or PALLAX alloy (white) for soldering with CEKA SOL FILIGRAN
Height: 2.43 mm - ø 2.25 mm - ø base: 3.2 mm
1201 C **ORAX ALLOY 1 pc**
1203 C **PALLAX ALLOY 1 pc**



PRECI-BALL/CLIX MALE PA
Spherical burn-out plastic male for incorporation into post-copings and for casting
Height: 2.4 mm - ø 2.25 mm - ø base: 3.2 mm
1205 C **1 pc**
1205 CB **50 pcs**



PRECI-BALL/CLIX MALE V AND V LONG
Spherical, removable male in TITANAX alloy for incorporation into an M2 base ring on post-copings
Height male V: 3.05 mm, male V long: 3.35 mm
ø 2.25 mm - Threads: M2 - Internal hex: 0.9 mm
1206 C **1 pc**
1206 CL **0.3 mm extra long 1 pc**



PRECI-BALL/CLIX BASE RING
M2 base ring in the high-fusing IRAX or NOPRAX alloy to incorporate the 1206 C PRECI-CLIX male V. For direct casting or for soldering.
Height: 1.3 mm - ø 3.4 mm - Threads: M2
RA 0063 **IRAX ALLOY 1 pc**
RA 0064 **NOPRAX ALLOY 1 pc**



PRECI-CLIX MALE PE
Spherical plastic male for incorporation into the male keeper and for casting
Height: 3.95 mm - ø 2.25 mm
1281 C **1 pc**



PRECI-CLIX MALE TI
Spherical titanium male for cementation into a cast male keeper. Use CEKA SITE.
Height: 3.95 mm - ø 2.25 mm
1271 C **1 pc**



IMPRESSION TOOL M2
Impression and cementation tool for the post/base ring. Total height: 7 mm - Threads: M2
RE H 2 **2 pcs**



MODEL ANALOGUE M2
Model analogue for the post/base ring.
To be used with the RE H 2 and the male.
Total height: 6 mm - Threads: M2
RE H 14 **2 pcs**



PRECI-BALL/CLIX CUP BURR
Burr to finish the 1205 C PRECI-BALL/CLIX male PA and the 1281 C PRECI-CLIX male PE
ø 2.35 mm
1230 **2 pcs**



PRECI-BALL/CLIX PARALLELING MANDREL MALE
Adjustable paralleling mandrel for males
ø 2.35 mm
1201 P **1 pc**



PRECI-BALL/CLIX PARALLELING MANDREL FEMALE
Adjustable paralleling mandrel for females.
To be used with diverging males.
ø 2.35 mm
1211 P **1 pc**



PRECI-BALL/CLIX PARALLELING MANDREL BASE RING
Paralleling mandrel for M2 base rings
ø 2.35 mm - Threads: M2
RE P 4 **1 pc**



PRECI-CLIX PARALLELING MANDREL MALE KEEPER
Paralleling mandrel for the RE 04 TI male keeper
ø 2.35 mm
RE P 7 **1 pc**



PRECI-BALL/CLIX SCREW-DRIVER FOR THREADED MALES
External hex: 0.9 mm - Length: 26 mm
IMP-XS-042 **1 pc**



PRECI-BALL/CLIX MALE ANALOGUE
Male analogue for the working model, including space maintainer
1201 D **2 pcs + 2 space maintainers**



PRECI-BALL ACTIVATING TOOL
Activating tool to tighten the PRECI-BALL segments
1220 **1 pc**



PRECI-BALL DEACTIVATING TOOL
Deactivating tool to spread the PRECI-BALL segments
1221 **1 pc**



PRECI-CLIX INSERTION TOOL
Insertion tool for the plastic females
Total height: 67.5 mm
1222 **1 pc**



PRECI-BALL/CLIX PROTECTION CAP
Protection cap in TITANAX alloy for threading into the base ring. ø 3 mm - Threads: M2
RE H 17 **2 pcs**


CEKA SITE
CEKA BOND
See page 18.

* See page 19 for table of alloys and materials.

PRECI-HORIX®

Burn-out plastic bar with elastic plastic riders.

The bar attachment allows a rotational and a slight vertical movement by compression of the plastic riders. The riders are easily replaceable and available in three retention levels.



PRECI-HORIX STANDARD

1701

2 plastic bar patterns
6 yellow riders
6 processing riders
1 insertion tool

KIT

PRECI-HORIX PLASTICWAX

1731

2 PLASTICWAX bar patterns
6 yellow riders
6 processing riders
1 insertion tool

KIT

PRECI-HORIX COMBI

1741

1 plastic bar pattern
2 yellow riders
2 processing riders
2 stainless steel housings
1 insertion tool

KIT

INDIVIDUAL COMPONENTS* & ACCESSORIES



PRECI-HORIX METAL HOUSING

Ultrathin stainless steel housing with titanium/nitrate layer (gold-coloured) for a perfect fit of the riders in the prosthesis. The housing is polymerized into acrylic resin (with the processing rider). Do not solder!

Length: 5 mm - Width: 5 mm
Thickness: 0.2 mm

1706
1706B

6 pcs
50 pcs

REDUCED HEIGHT



PRECI-HORIX PLASTIC PATTERN

Burn-out plastic bar pattern which may be reduced to facilitate incorporation into close bite situations. Cast in any hard alloy. Bar height: 4 mm - Length: 50 mm
ø 1.8 mm

1704
1704B

6 pcs
50 pcs



PRECI-HORIX RIDER

Polypropylene

Height: 2.87 mm - Length: 5 mm
ø 3.3 mm

Available in three retention levels:

normal retention:
1802 yellow 6 pcs
1802B yellow 50 pcs
reduced retention:
1805 white 6 pcs
1805B white 50 pcs
increased retention:
1806 red 6 pcs
1806B red 50 pcs
combination package:
1807 2 + 2 + 2 pcs



PRECI-HORIX PLASTICWAX PATTERN

Bar pattern in PLASTICWAX which may be reduced to facilitate incorporation into close bite situations.

Ideal for use with fast set investments. Cast in any hard alloy.

Bar height: 8.25 mm (may be reduced to 3 mm) - Length: 50 mm - ø 1.8 mm

1734
1734B

4 pcs
50 pcs



PRECI-HORIX PATTERN ANALOGUE

Plastic pattern analogue for the working model, to be used in case of repair and relining, or when making a new prosthesis.

Height: 8.25 mm - Length: 50 mm
ø 1.8 mm

1707

2 pcs



PRECI-HORIX PROCESSING RIDER

Adapt the plastic processing rider to the bar prior to polymerization.

Length: 5 mm (may be reduced to fit the bar height)

1703
1703B

6 pcs
50 pcs



PRECI-HORIX INSERTION TOOL

Insertion tool for the 3 rider types

1705

2 pcs



PRECI-HORIX PARALLELING MANDREL

Paralleling mandrel for bars. Ideal for paralleling multiple pattern sections.
ø 2.35 mm

1708

1 pc

PRECI-BAR

Bar attachment in two sizes: MINI and STANDARD.

The bar is either rigid (U-shaped) or resilient (oval). A choice of three alloys for the rider.

The bars in gold alloy/palladium alloy can be soldered with CEKA SOL FILIGRAN (yellow) or CEKA SOL W (white), or cast (burn-out plastic).

The metal bars are available in two lengths: 50 mm and 200 mm.

MINI PROFILES

Height: 2.3 mm
Width: 1.6 mm



ORAX* RESILIENT OVAL MINI BAR
1103/B/OR 50 mm
1103/BL/OR 200 mm



PALLAX* RESILIENT OVAL MINI BAR
1103/B/PA 50 mm
1103/BL/PA 200 mm



PLASTIC RESILIENT OVAL MINI BAR
1012/B 4 x 50 mm

NEW

MINI RIDERS

Height: 2.8 mm
Width: 4 mm



ORAX* MINI RIDER
1102/H/MR/OR 50 mm



PALLAX* MINI RIDER
1102/H/MR/PA 50 mm



STAINLESS STEEL* MINI RIDER
1102/H/MR/IN 50 mm


NEW

STANDARD PROFILES

Height: 3 mm
Width: 2.2 mm



ORAX* RESILIENT OVAL STANDARD BAR
1101/B/OR 50 mm
1101/BL/OR 200 mm



PALLAX* RESILIENT OVAL STANDARD BAR
1101/B/PA 50 mm
1101/BL/PA 200 mm



PLASTIC RESILIENT OVAL STANDARD BAR
1013/B 4 x 50 mm

NEW

STANDARD RIDERS


Height: 3.5 mm
Width: 5 mm



ORAX* STANDARD RIDER
1100/H/MR/OR 50 mm



PALLAX* STANDARD RIDER
1100/H/MR/PA 50 mm



STAINLESS STEEL* STANDARD RIDER
1100/H/MR/IN 50 mm

NEW

ORAX* RIGID U-SHAPED STANDARD BAR
1100/B/OR 50 mm
1100/BL/OR 200 mm

PALLAX* RIGID U-SHAPED STANDARD BAR
1100/B/PA 50 mm
1100/BL/PA 200 mm

PLASTIC RIGID U-SHAPED STANDARD BAR
1011/B 4 x 50 mm

NEW

* TABLE OF ALLOYS

ORAX - Yellow - Au 70 - Pt 5 - Ag 12 - Cu 13

Heat treatment: 60 min at 400 °C (752 °F)

Melting range: 910-955 °C (1670-1823 °F)

PALLAX - White - Au 2 - Ag 37 - Pt 9.5 - Pd 37 - Cu 12.5 - Co 2

Melting range: 1055-1130 °C (1931-2066 °F)

STAINLESS STEEL - White - Fe 73 - Cr 18 - Ni 8 - Mo, Cu, C, Mn and Si 1

Do not heat!

PARALLELING MANDRELS

1100 P

Paralleling mandrel for STANDARD bars

1102 P

Paralleling mandrel for MINI bars



PRECI-CLIP

Round bar attachment with adjustable rider.
The rider is available with occlusal or lateral retention for acrylic fixation.
The riders are available in gold alloy or stainless steel.
The profile can be soldered with CEKA SOL FILIGRAN, laser-welded or cast in any hard alloy.



PRECI-CLIP RIDER LA

Adjustable rider with lateral retention for acrylic resin for minimum incorporation possibilities.
Do not solder the rider! Height: 3.65 mm - Length: 3.5 mm - Space maintainer: 0.7 mm

Available in:

# 1105	ORAX* ALLOY	2 pcs + 2 space maintainers
# 1105AB	ORAX* ALLOY	20 pcs + 20 space maintainers
# 1106	STAINLESS STEEL*	2 pcs + 2 space maintainers
# 1106AB	STAINLESS STEEL*	20 pcs + 20 space maintainers

NEW



PRECI-CLIP RIDER OC

Adjustable rider with occlusal retention for acrylic resin for minimum incorporation possibilities.
Do not solder the rider! Height: 3.65 mm - Length: 3.5 mm - Space maintainer: 0.7 mm

Available in:

# 1125	ORAX* ALLOY	2 pcs + 2 space maintainers
# 1125AB	ORAX* ALLOY	20 pcs + 20 space maintainers
# 1126	STAINLESS STEEL*	2 pcs + 2 space maintainers
# 1126AB	STAINLESS STEEL*	20 pcs + 20 space maintainers



PRECI-CLIP BAR PROFILE

Round bar profile in ORAX* alloy for soldering with CEKA SOL FILIGRAN or in pure titanium for the laser technique

Length: 50 mm - ø 1.8 mm

# 1105/B	ORAX* ALLOY	1 pc
# 1109/B	PURE TITANIUM*	1 pc



PRECI-CLIP BAR PATTERN

Round plastic bar pattern for casting in any hard alloy between natural abutments and between implants

Length: 50 mm - ø 1.8 mm

# 1014/B	4 pcs
----------	-------



PRECI-CLIP PATTERN ANALOGUE

Pattern analogue in hard isolating plastic for the working model, to be used in case of repair and relining, or when making a new prosthesis.

Height: 8.25 mm - Length: 50 mm - ø 1.8 mm

# 1707	2 pcs
--------	-------

PRECI-TUBIX/MORTIX

Intracoronary, plastic slide attachment for sectioned bridges and diverging abutments



PRECI-MORTIX N

Conical
Height: 7 mm (may be reduced)
Total width: 2.85 mm
Cone: 2°23'

# 10002	6 pcs
---------	-------



PRECI-TUBIX N

Cylindrical, small
Ideal for use in the anterior region.
Height: 7 mm (may be reduced)
Total width: 2 mm
ø male: 1.05 mm

# 10001	6 pcs
---------	-------



PRECI-TUBIX M

Cylindrical, large, **reversible**
Height: 6 mm (may be reduced)
Total width: 3 mm
ø male: 1.45 mm

# 10004	6 pcs
---------	-------

PRECI-TUBIX MORTIX COMBI

Combination package

# 10005	2 x 10001, 2 x 10002, 2 x 10004
---------	---------------------------------

PRECI-POST M

Rational system with a conicity of 2°30' over the entire useful length.

Form and dimensions according to Dr Mooser. For post-copings and temporary post cores with one or more roots.
Yellow and blue colour codification.



PRECI-POST M SET

- # 2001**
1 yellow reamer
1 blue reamer
25 yellow opaque impression posts
25 blue opaque impression posts
25 yellow transparent laboratory posts
25 blue transparent laboratory posts



PRECI-POST M LABORATORY POST

Transparent plastic laboratory posts, to be used also for direct method in the mouth

- # 2003GL 50 pcs** yellow tip ø 0.80 mm, cone length 10.70 mm, total length 18.60 mm
2003BL 50 pcs blue tip ø 1.00 mm, cone length 12.30 mm, total length 22.90 mm
2003L 2 x 50 pcs combination package yellow & blue



PRECI-POST M IMPRESSION POST

Opaque plastic impression posts (with retention), to be used with any impression technique (including silverplating and epoxy)

- # 2002G 50 pcs** yellow tip ø 0.80 mm, length 14.10 mm
2002B 50 pcs blue tip ø 1.00 mm, length 16.70 mm
2002 2 x 50 pcs combination package yellow & blue



PRECI-POST M AUXILIARY POST

Stainless steel posts (with flat head) for temporary restorations

- # 2500 20 pcs** yellow tip ø 0.85 mm, cone length 7.40 mm, total length 11 mm
2501 20 pcs yellow tip ø 0.85 mm, cone length 8.50 mm, total length 13 mm
2501B 20 pcs yellow tip ø 0.85 mm, cone length 10.70 mm, total length 15 mm
2502 20 pcs blue tip ø 1.05 mm, cone length 10.70 mm, total length 16 mm
2502B 20 pcs blue tip ø 1.05 mm, cone length 11.80 mm, total length 17 mm
2503 20 pcs blue tip ø 1.05 mm, cone length 12.80 mm, total length 19 mm



PRECI-POST M REAMER

Reamer according to the Mooser system

- # 2004G 1 pc** yellow tip ø 0.80 mm
2004B 1 pc blue tip ø 1.00 mm

PRECI-POST CC

Cylindro-conical system: 5°30' at the base and then cylindrical over the entire useful length for optimum retention.

For post-copings and temporary post cores with one or more roots.

Yellow, red, blue, and green colour codification.



PRECI-POST CC SET

- # 2050** 50 yellow posts, 50 red posts, 50 blue posts, 50 green posts
2060 20 yellow posts, 15 red posts, 10 blue posts, 5 green posts



PRECI-POST CC PLASTIC POST

Plastic posts for the laboratory

- # 2051A 50 pcs** yellow ø 1.40 mm, tip ø 0.65 mm, cone L 4.60 mm, total L 16.60 mm
2052B 50 pcs red ø 1.60 mm, tip ø 0.70 mm, cone L 5.30 mm, total L 18.60 mm
2053C 50 pcs blue ø 1.80 mm, tip ø 0.75 mm, cone L 6.30 mm, total L 20.00 mm
2054D 50 pcs green ø 2.00 mm, tip ø 0.80 mm, cone L 7.05 mm, total L 22.40 mm



PRECI-POST CC AUXILIARY POST

Stainless steel posts for temporary restorations

- # 2551A 20 pcs** ø 1.40 mm, tip ø 0.70 mm, cone length 4.40 mm, total length 11 mm
2552B 20 pcs red ø 1.60 mm, tip ø 0.75 mm, cone length 5.30 mm, total length 13 mm
2553C 20 pcs blue ø 1.80 mm, tip ø 0.80 mm, cone length 6.20 mm, total length 15 mm
2554D 20 pcs green ø 2.00 mm, tip ø 0.80 mm, cone length 7.10 mm, total length 17 mm



PRECI-POST CC REAMER

Cylindro-conical reamer

- # 2951A 1 pc** yellow tip ø 0.65 mm
2952B 1 pc red tip ø 0.70 mm
2953C 1 pc blue tip ø 0.75 mm
2954D 1 pc green tip ø 0.80 mm

CEKA SITE



CEKA SITE is an anaerobic bonding composite.

Mix for 30 seconds (1:1) and apply to sandblasted surfaces within 1 minute.
Hold for 10 minutes.
Excess material can be easily removed.
Store refrigerated but use at room temperature.

CEKA SITE 2 x 2 g



CEKA BOND

NEW



CEKA BOND is an anaerobic adhesive to prevent gradual unthreading of prosthetic components.

The components can still be unthreaded by using the proper instruments.

Setting time in the mouth: 3 hours

CB1 5 ml



3C-BOND



Bonding agent for porcelain firing to titanium-free, non-precious alloys (Cr-Co-Mo and Ni-Cr).

Avoids greying/greening of porcelain.
Apply the material as a wash opaque.

140-3CB-20 20 g




PERMA-RET



Mechanical retention for acrylic and composite teeth.
Ideal for single tooth repairs or in deep bites.

1601 Set: 1 wire holder, 3 twist drills
 100 cm of threaded silver wire
1602 13 x 80 mm of threaded silver wire
1604 1 wire holder
1606 3 twist drills



PLASTICWAX



Wax with plastic filler.

Ideal for build-up and milling technique.

Available as build-up wax or in 8° profiles (height: 4.5 mm - length: 60 mm - width top: 1.9 mm / bottom: 2.8 mm).

IMP-CK-045 box 45 g
IMP-CK-014 8° profiles 4 pcs



EXPANDO



Expando is a retraction device to protect the lips, cheek, and tongue during dental treatment procedures. Expando helps to relax the patient and also enables a better positioning of the suction device. After placing the expando, the dentist has better access to the treatment area and can keep both hands free to operate. Restorative work can be done in the molar area without chairside assistance. Can be sterilized.

Available in 3 sizes:

7301 small 1 pc
7302 medium 1 pc
7303 large 1 pc



PRECI-PROFILE



LASER WELDING TITANIUM PROFILES FOR WRAPAROUND IMPLANT BRIDGES

To be used with the CS31 titanium laser welding alloy.
Fast, versatile and economical. Pure titanium grade 2
Height: 2.9 mm - Width: 2 mm - Length: 50 mm - Vickers hardness: 210 ± 20

STRAIGHT TITANIUM PROFILE FOR LASER WELDING

IMP-CK-015 1 pc
IMP-CK-025 25 pcs

CURVED TITANIUM PROFILE FOR LASER WELDING

IMP-CK-016 1 pc
IMP-CK-026 25 pcs
Curve radius: 20 mm - Heat-treated



CEKA SOL

CEKA SOL is a complete range of low-fusing tube solders for multiple applications. The incorporated flux provides for easy soldering of dissimilar metals. Also available as addition solder for laser welding.



LOW-FUSING TUBE SOLDER WITH FLUX INCORPORATED

# CS00	CEKA SOL	yellow	780-820 °C (1436-1508 °F)
	ø 1.15 mm 2 x 25 cm	Au 80 - Cu 13 - In 5 - Zn 2	
# CS00 F	CEKA SOL FILIGRAN	yellow	780-820 °C (1436-1508 °F)
	ø 0.9 mm 2 x 25 cm	Au 80 - Cu 13 - In 5 - Zn 2 (contains less flux)	
# CS22	CEKA SOL W	white	865-930 °C (1589-1706 °F)
	ø 1.15 mm 2 x 25 cm	Au 76.5 - Cu 0.4 - Zn 6.5 - Ni 16.6	
# CS21	CEKA SOL L	yellow	615-630 °C (1139-1166 °F)
	ø 1.15 mm 2 x 25 cm	Au 42 - Ag 38.5 - Zn 11 - In 8.5	
# CS20	CEKA SOL G	yellow	755-820 °C (1391-1508 °F)
	ø 1.15 mm 2 x 25 cm	Au 68 - Ag 13.3 - Cu 12.8 - Sn 1 - Zn 4.9	
# CS23	CEKA SOL CR	white	1000-1030 °C (1832-1886 °F)
	ø 1.15 mm 4 x 25 cm	Au 10 - Ag 37 - Pd 37 - Cu 12 - Zn 4	

PRECIOUS	NON-PRECIOUS	CR-CO	STAINLESS STEEL
X	X	X	X
X	X	X	X
X	X	X	X
X		X	X
X	X		
		X	

ADDITION ALLOY FOR LASER WELDING

NEW

# CS31	CEKA SOL T1	white	pure titanium
	ø 0.4 mm 8 x 25 cm		
# CS32	CEKA SOL OR	yellow	910-995 °C (1670-1823 °F)
	ø 0.4 mm 2 x 25 cm	Au 70 - Pt 5 - Ag 12 - Cu 13	
# CS33	CEKA SOL PA	white	1055-1130 °C (1931-2066 °F)
	ø 0.4 mm 2 x 25 cm	Au 2 - Pt 9.5 - Ag 37 - Pd 37 - Cu 12.5 - Co 2	

TABLE OF ALLOYS AND MATERIALS

PALLAX 1055-1130 °C 1931-2066 °F	For soldering to precious and non-precious alloys White - Au 2 - Ag 37 - Pt 9.5 - Pd 37 - Cu 12.5 - Co 2	PLATIRAX 1790-1820 °C 3254-3308 °F	For the cast-on technique with all dental alloys White - Pt 85 - Ir 15
IRAX 1400-1460 °C 2552-2660 °F	For the cast-on technique with precious alloys only White - Au 60 - Pt 24 - Pd 15 - Ir 1	STAINLESS STEEL Do not heat!	Only for bonding and acrylic fixation White - Fe 66 - Cr 17 - Ni 11 - Mo 2 - other 4
NOPRAX 1355-1450 °C 2471-2642 °F	For the cast-on technique with non-precious alloys only White - Ni 72 - Cr 17 - Fe 10 - Mn 1	POLYPROPYLENE	Females of PRECI-HORIX/VERTIX # 1802, 1805, 1806
TITANAX Do not heat!	Only for bonding and acrylic fixation White - Ti 90 - Al 6 - V 4	POLYACETAL	Females of PRECI-CLIX/SAGIX # 1231, 1232, 1233, 1311, 1312, 1313, 1361, 1362, 1363
ORAX 910-955 °C 1670-1823 °F	Heat treatment: 60 min at 400 °C (752 °F) Yellow - Au 70 - Pt 5 - Ag 12 - Cu 13	THERMOPLASTIC ELASTOMER	Processing ring of PRECI-BALL # 1201 B

WWW.CEKA-PRECILINE.COM

SWISS MADE



CE 0470



CEKA REVAX
CEKA
PRECI-VERTIX
PRECI-VERTIX AT
PRECI-SAGIX
PRECI-BALL
PRECI-CLIX RADICULAR
PRECI-CLIX RADICULAR RC
PRECI-CLIX AXIAL
PRECI-CLIX EXTRACORONAL
PRECI-HORIX
PRECI-BAR
PRECI-CLIP
PRECI-TUBIX/MORTIX
PRECI-POST
3C-BOND
PERMA-RET
EXPANDO
PRECI-PROFILE
CEKA SOL

CATALOGUE

Prospectus n° 269.E-ed.E
Copyright© ALPHADENT NV 6/2011
BTW BE 0414.789.321 RPR Kortrijk

ALPHADENT NV
Textielstraat 24
8790 Waregem, Belgium
tel +32 56 629 100
fax +32 56 629 101
e-mail: info@ceka-preciline.com